

**DP-8025**  
Multifunction Printer



---

## General

<b>Type</b>	Desktop
<b>Copy/Print Process</b>	Laser Indirect Electrostatic
<b>Developing Process</b>	Dry Dual Component
<b>Inverting Automatic Document Feeder</b>	50 sheets (A4, 80g/m <sup>2</sup> )

## Power Supply

<b>Hertz</b>	50/60 Hz
<b>Voltage (V)</b>	AC 220 - 240 V

## Power Consumption

<b>Maximum</b>	Less then 1,5 KW
<b>Power save mode</b>	Approx. 28 W
<b>Sleep Mode</b>	Approx. 18 W
<b>Warmup Time</b>	Approx. 35 sec. (Main power switch ON), approx. 30 sec. (Power saver mode)

## Dimensions (mm)

<b>Width</b>	599.0
<b>Depth</b>	707.0
<b>Height</b>	697.0

---

Weight (kg)	82.0
-------------	------

## Digital Copier

### First Copy Speed (secs.)

B/W	4.5
-----	-----

### Resolution

600 x 600 dpi	yes
---------------	-----

Greyscale	256 steps
-----------	-----------

### Multi-Copy Speed (ppm)

B/W	25.0
-----	------

Maximum Original Size	A3
-----------------------	----

Copy Size	A3 - A5 (fixed)
-----------	-----------------

### Copy Ratio

Enlargement	200%, 173%, 141%, 122%, 115%
-------------	------------------------------

Reduction	87%, 82%, 71%, 58%, 50%
-----------	-------------------------

Zoom	25 - 400% (in 1% increments)
------	------------------------------

Multiple Copy	1 to 999, Automatic reset to 1
---------------	--------------------------------

Exposure Control	Text, Text/Photo, Photo
------------------	-------------------------

### Paper Capacity

Standard	550-sheet paper tray x 2 + 50-sheet bypass
----------	--

Maximum	2,250 sheets with option
---------	--------------------------

### Sort Memory Capacity (Mb)

Standard	16.0
----------	------

Maximum	144.0
---------	-------

### Printer

Network Printer Interface	Ethernet 10Base-T/100Base-TX
---------------------------	------------------------------

Communication Protocol	TCP/IP (LPD [Port9100/RAW], SNMP, DHCP); AppleTalk (PS), IPP (PCL, PS)
------------------------	--

Local Printer Interface	USB 1.1
-------------------------	---------

### Page Description Language

Standard	Panasonic Printing System for Windows
----------	---------------------------------------

Option	PCL 5e Emulation, PCL6 Emulation, Adobe PostScript 3
--------	--

### Speed (ppm)

B/W	25.0
-----	------

## Paper Size

<b>Paper Tray</b>	A3 - A5
<b>Bypass</b>	A3 - A5
<b>Printing Resolution</b>	1,200 dpi equivalent x 600 dpi (PCL, PS), 600 dpi x 600 dpi, 300 dpi x 300 dpi

## Printer Memory (Mb)

<b>Standard</b>	50.0
<b>Compatible client Operating Systems</b>	Windows Vista/XP/2000/Server 2003, MacOS 8.6 - 10.5 (PS Only)

## Scanner

<b>Network Scanner Interface</b>	Ethernet 10Base-T/100Base-TX
<b>Communication Protocol</b>	TCP/IP (LPR, FTP)
<b>Maximum Scanning Size</b>	A3

## Scanning Speed

<b>B/W</b>	approx. 32 opm (Originals per minute - A4 portrait with ADF)
<b>Scanning Resolution</b>	150 dpi x 150 dpi, 300 dpi x 300 dpi, 600 dpi x 600 dpi
<b>Compatible Client Operating Systems</b>	Windows Vista/XP/2000/Server 2003

## Data Format

<b>B/W</b>	TIFF, PDF
------------	-----------

## Fax

## Compatibility

<b>G3 Fax</b>	ITU-T Group 3, ECM
<b>Internet Fax</b>	IETF RFC 3965, ITU-T T.37
<b>Communication Protocol</b>	TCP/IP (SMTP, POP3, LDAP)
<b>Modem Speed</b>	33.6 - 2.4 kbps with automatic fallback
<b>Coding Scheme</b>	JBIG / MMR / MR / MH
<b>Scanning Speed</b>	Approx. 0.7 sec.(A4 portrait in Standard or Fine mode with ADF)
<b>Transmission Speed</b>	Approx 2.9 sec. (A4)

## Scanning Resolution

<b>Standard</b>	8 dots/mm x 3.85 lines/mm
<b>Fine</b>	8 dots/mm x 7.7 lines/mm
<b>Super Fine</b>	16 dots/mm x 15.4 lines/mm
<b>600dpi</b>	600 dpi x 600 dpi
<b>Maximum Original Size</b>	A3
<b>Effective Scanning Width</b>	292 mm
<b>Recording Resolution</b>	600 x 600 dpi

<b>Standard Memory</b>	3 MB (Approx. 180 pages)
<b>Optional Memory</b>	Base memory plus 4 MB (320 pages)/8 MB (640 pages)
<b>Data Format</b>	TIFF-FX (Profile S/F/J), PDF

