

**DP-8032**  
Multifunction Copier



---

## General

<b>Type</b>	Desktop
<b>Copy/Print Process</b>	Laser Indirect Electrostatic
<b>Developing Process</b>	Dry Dual Component
<b>Inverting Automatic Document Feeder</b>	50 sheets (A4, 80g/m <sup>2</sup> )

---

## Digital Copier

---

### First Copy Speed (secs.)

<b>B/W</b>	4.5
------------	-----

---

### Resolution

<b>600 x 600 dpi</b>	yes
<b>Greyscale</b>	256 steps

---

### Multi-Copy Speed (ppm)

<b>B/W</b>	32.0
<b>Maximum Original Size</b>	A3
<b>Copy Size</b>	A3 - A5 (fixed)

---

## Copy Ratio

<b>Enlargement</b>	200%, 173%, 141%, 122%, 115%
<b>Reduction</b>	87%, 82%, 71%, 58%, 50%
<b>Zoom</b>	25-400% (in 1% increments)
<b>Multiple Copy</b>	1 to 999, Automatic reset to 1
<b>Exposure Control</b>	Text, Text/Photo, Photo

## Paper Capacity

<b>Standard</b>	550-sheet paper tray x 2 + 50-sheet bypass
<b>Maximum</b>	2,250 sheets with option

## Sort Memory Capacity (Mb)

<b>Standard</b>	16.0
<b>Maximum</b>	144.0

## Printer

<b>Network Printer Interface</b>	Ethernet 10Base-T/100Base-TX
<b>Communication Protocol</b>	TCP/IP (LPD [Port9100/RAW], SNMP, DHCP)
<b>Local Printer Interface</b>	USB 1.1

## Page Description Language

<b>Standard</b>	Panasonic Printing System for Windows
<b>Option</b>	PCL 5e Emulation, PCL 6 Emulation, Adobe PostScript 3

## Speed (ppm)

<b>B/W</b>	32.0
------------	------

## Paper Size

<b>Paper Tray</b>	A3 - A5
<b>Bypass</b>	A3 - A5
<b>Printing Resolution</b>	1,200 dpi equivalent x 600 dpi (PCL, PS), 600 dpi x 600 dpi, 300 dpi x 300 dpi

## Printer Memory (Mb)

<b>Standard</b>	50.0
-----------------	------

**Compatible client Operating Systems**-Windows Vista/XP/2000/Server 2003, MacOS 8.6 - 10.5 (PS Only)

## Scanner

<b>Network Scanner Interface</b>	Ethernet 10Base-T/100Base-TX
<b>Communication Protocol</b>	TCP/IP, (LPR, FTP)
<b>Maximum Scanning Size</b>	A3

## Scanning Speed

<b>B/W</b>	Approx. 32 opm (Originals per minute - A4 portrait with ADF)
<b>Scanning Resolution</b>	150 dpi x 150 dpi, 300 dpi x 300 dpi, 600 dpi x 600 dpi
<b>Compatible Client Operating Systems</b>	Windows Vista/XP/2000/Server 2003

## Data Format

<b>B/W</b>	TIFF, PDF
------------	-----------

## Fax

## Compatibility

<b>G3 Fax</b>	ITU-T Group 3, ECM
<b>Internet Fax</b>	IETF RFC 3965, ITU-T T.37
<b>Communication Protocol</b>	TCP/IP (SMTP, POP3, LDAP)
<b>Modem Speed</b>	33.6 - 2.4 kbps with automatic fallback
<b>Coding Scheme</b>	JBIG / MMR / MR / MH
<b>Scanning Speed</b>	Approx. 0.7 sec. (A4 portrait in Standard or Fine mode with ADF)
<b>Transmission Speed</b>	Approx. 2.9 sec. (A4)

## Scanning Resolution

<b>Standard</b>	8 dots/mm x 3.85 lines/mm
<b>Fine</b>	8 dots/mm x 7.7 lines/mm
<b>Super Fine</b>	16 dots/mm x 15.4 lines/mm
<b>600dpi</b>	600 dpi x 600 dpi
<b>Maximum Original Size</b>	A3
<b>Effective Scanning Width</b>	292 mm
<b>Recording Resolution</b>	600 x 600 dpi
<b>Standard Memory</b>	3 MB (Approx. 180 pages)
<b>Optional Memory</b>	Base memory plus 4 MB (320 pages)/8 MB (640 pages)
<b>Data Format</b>	TIFF-FX (Profile S/F/J), PDF