

# PRINT COLOUR FAST!

YOU WILL BE IMPRESSED WITH THE ARRAY OF FUNCTIONS OF OUR A3 COLOUR MULTIFUNCTIONAL SYSTEMS 6505ci AND 7505ci: PRINTING, SCANNING – EVEN WHEN ON THE MOVE VIA WIFI\* – COPYING OR FAXING\*, COMBINED WITH OPTIONAL HARDWARE AND SOFTWARE SOLUTIONS: EVERYTHING CAN BE TAILORED TO SUIT YOUR OWN SPECIFIC NEEDS.

COLOUR PHOTOS AND AREAS SHINE WITH EXCELLENT QUALITY, WHILE ENTIRE STACKS OF PRINT JOBS ARE COMPLETED IN THE BLINK OF AN EYE. IF YOU ARE LOOKING FOR REALLY CONVINCING RESULTS, THESE SYSTEMS ARE THE RIGHT CHOICE FOR YOU!



## HIGHLIGHTS:



**Score points with appealing colour documents:** Take advantage of positive image effects and optimise your communication with customers and business partners.

Consistently solid colour, the use of different colour charts and the colour management with the Fiery® Controller\* all ensure noticeably better colour quality with impressive speed, even for large-volume print jobs.



**Handle large print volumes easily:** Brochures, form letters, budgets, exposés, presentations, etc., are finished in the blink of an eye. Take advantage of professional finishing\* and you will give your print jobs an excellent finishing touch.



**Professional paper management:** Benefit from the high paper capacities of up to 7,650 pages from 8 paper feeds\* for up to 8 types of paper and even replace your toner cartridges during on-going operations. Print special formats up to A3+ as well as intermediate formats from the cassette, paper weights up to 300 g/m<sup>2</sup>, tab sheets and banner paper, and define up to 50 dividers in just one print job.



**High output speeds:** Up to 70 colour A4 pages/minute and up to 35 colour A3 pages/minute (7505ci); 100% duplex productivity, short warm-up times and output of the first colour copies after just 6.2/5.9 seconds (6505ci/7505ci) ensure that complex production tasks can be completed rapidly. The standard dual scan original feeder scans up to 120 single-sided A4 original pages/minute.



**Customised functionality:** It is easy to integrate optional software solutions for scanning, productivity and security using the HyPAS interface – all in exact accordance with your individual needs. Save time and money with solutions for Follow-Me-Printing\* within the network or for creating text-searchable documents when scanning.

DIGITAL   
 MULTIFUNCTIONAL COLOUR SYSTEM  
**6505ci / 7505ci**  
 Copy / Print / Scan / Fax  
 A3

\* optional

# 6505ci / 7505ci

## TECHNICAL DATA

IF IT WORX, IT'S  
**UTAX**

### General

|                              |   |
|------------------------------|---|
| <b>Type</b>                  | Console Unit  |
| <b>Function</b>              | Copy, print, scan, optional: fax  |
| <b>Print technology</b>      | Laser colour and b/w  |
| <b>Original format</b>       | max A3 from platen glass  |
| <b>Original feeder</b>       | Document processor with simultaneous duplex scanning (A6R-A3, capacity: 270 sheet A4, paper weight 35-220 g/m <sup>2</sup> )  |
| <b>Copy/print speed</b>      | 6505ci: max 65 A4 pages/min and max 32 A3 pages/min in colour and b/w<br>7505ci: max 70 A4 pages/min and max 35 A3 pages/min in colour and max 75 A4 pages/min and max 37 A3 pages/min in b/w |
| <b>1st page (copy/print)</b> | Colour: 6.2/6.3 seconds*, b/w: 5.4/5.3 seconds* (6505ci)<br>Colour: 5.9/6.1 seconds*, b/w: 4.8/4.9 seconds* (7505ci)  |
| <b>Warm-up time</b>          | 60 seconds  |
| <b>Copy resolution</b>       | 600 x 600 dpi, 9,600 x 600 dpi level  |
| <b>Greyscale</b>             | 256   |
| <b>Paper feed</b>            | 2 x 500 sheet universal cassettes (A5R-A3+ [max 305 x 457 mm]),<br>2 x 1,500 sheet large capacity cassettes (A4), 150 sheet multi-bypass (A6R-A3+, Banner [305 x 1,219 mm])                   |
| <b>Paper weights</b>         | Universal cassette 60-256 g/m <sup>2</sup> , multi-bypass 60-300 g/m <sup>2</sup> , duplex 60-256 g/m <sup>2</sup>  |
| <b>Paper output</b>          | 250 sheet A4 (upper tray), 100 sheet (lower tray) with Copy tray type D   |
| <b>System memory</b>         | 4 GB RAM, 320 GB HDD**  |
| <b>Continuous copying</b>    | 1-9,999 copies  |
| <b>Zoom</b>                  | 25%-400% in steps of 1%   |
| <b>Functions</b>             | Adjustable touch screen, duplex, 1,000 management codes, multi tasking controller, direct printing from USB stick, colour optimizer for printing, etc.  |

### Dimensions/Weight

|                   |                                    |
|-------------------|------------------------------------|
| <b>Dimensions</b> | 1,347 x 1,039 x 801 mm (H x W x D) |
| <b>Weight</b>     | approx. 190 kg                     |

### Environment

|                          |   |
|--------------------------|---|
| <b>Mains voltage</b>     | 220/240 V, 50/60 Hz   |
| <b>Power consumption</b> | approx. 2,400 max, approx. 1,480 W (6505ci)/1,630 W (7505ci) in operation, approx. 300 W in stand-by mode, approx. 11 W in sleep mode |

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.

UTAX Norderstedt  
[www.utax.com](http://www.utax.com)

### Print system

|                          |  |
|--------------------------|--|
| <b>Safety</b>            | GS/TÜV, CE   |
| <b>Type</b>              | Integrated within the system   |
| <b>Print format</b>      | A6R-A3+  |
| <b>Print resolution</b>  | 600 x 600 dpi, 9,600 x 600 dpi level   |
| <b>Processor</b>         | Freescale QorIQ P1022 (Dual Core) 1.067 MHz  |
| <b>Interfaces</b>        | USB 2.0, 10/100/1000BaseTX, USB host   |
| <b>Network protocols</b> | TCP/IP, IPX/SPX, Net BEUI  |
| <b>Operating systems</b> | Windows XP, Vista, Windows 7/8/8.1, Server 2003/2008 R2/2012 R2, Novell NetWare, Linux, Mac ex OS 10.4 |
| <b>Emulations</b>        | PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc                                    |
| <b>Functions</b>         | PDF/XPS direct printing, printing of e-mails, private printing, barcode printing                       |

### Scan system

|                          |  |
|--------------------------|--|
| <b>Scan type</b>         | CCD colour and b/w   |
| <b>Scan format</b>       | max A3   |
| <b>Scan speed</b>        | max. 120/200 A4 originals/min. (simplex/duplex) in colour and b/w (300dpi)   |
| <b>Scan resolution</b>   | 200 dpi, 300 dpi, 400 dpi, 600 dpi   |
| <b>Scan mode</b>         | Photo, text, photo/text, OCR   |
| <b>File types</b>        | TIFF, PDF, PDF/A, JPEG, XPS  |
| <b>Interface</b>         | 10/100/1000BaseTX  |
| <b>Network protocol</b>  | TCP/IP   |
| <b>Operating systems</b> | Windows XP, Vista, Windows 7/8, Server 2003/2008 R2/2012   |
| <b>Functions</b>         | Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan (Windows Vista, Windows 7/8, Server 2008 R2/2012), SMTP authentication, LDAP, PDF compression and encryption |

### Optional fax system (W) B

|                           |                              |
|---------------------------|------------------------------|
| <b>Compatibility</b>      | Super G3                     |
| <b>Original format</b>    | max A3                       |
| <b>Modem speed</b>        | 33.6 kbps                    |
| <b>Transmission speed</b> | 3 seconds or less using JBIG |
| <b>Compression method</b> | JBIG, MMR, MR, MH            |

### Optional fax system (W) B

|                          |  |
|--------------------------|--|
| <b>Fax resolution</b>    | Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi  |
| <b>Fax memory</b>        | 12 MB (max 120 MB)   |
| <b>Abbreviated dial</b>  | 2,000 numbers  |
| <b>One touch dial</b>    | 1,000 numbers  |
| <b>Group dial</b>        | 500 numbers  |
| <b>Operating systems</b> | Windows XP, Vista, Windows 7/8/8.1, Server 2003/2008 R2/2012 R2  |
| <b>Functions</b>         | Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception |

### Options

|                      |  |
|----------------------|--|
| <b>Finisher</b>      | DF-790 (C) (capacity: 4,000 sheet A4, stapling max 65 sheet A4), PH-7C hole punch unit for DF-790 (C), BF-730 brochure module for DF-790 (C) (max 16 sheet saddle stitching and folding A4/A3, tri-folding max 5 sheet A4), MT-730 (B) multi tray for DF-790 (C)   |
| <b>Paper feed</b>    | PF-730 (B) (2 x 500 sheet universal cassettes (A5R-A3+)), PF-740 (B) (2 x 1,500 sheet large capacity cassettes (A4)), PF-780 (B) (500 sheet multi-purpose cassette (A5R-A3+), required if PF-730 (B)/PF-740 (B) is installed), PF-770 (B) (3,000 sheet large capacity tray (A4), side deck)  |
| <b>Other options</b> | Data security kit (E), Internet fax kit (A), Printed document guard kit (B), Card authentication kit (B), Card reader holder (E), Keyboard holder (C), Banner guide (A), UG-33 ThinPrint® kit, UG-34 Emulation option kit, IB-50 Gigabit Ethernet card, IB-51 WLAN card, Copy tray type D, Fiery® Controller (Printing System 14 depends on Printing System Interface Kit (B)) |

\* Depending on operating status.

\*\* For copy, print, scan, fax.

Specifications subject to change without notice.

Image shows machine with optional accessories.

The 6505ci and 7505ci are manufactured in accordance with the requirements of the Energy Star Program.



Your UTAX dealer

HyPAS™

