

QUICK SKIM – THEN PRINT.

KEEP THESE NUMBERS IN MIND: 6555i AND 8055i. BECAUSE OUR A3 B/W MULTIFUNCTIONAL SYSTEMS DELIVER EXCELLENT RESULTS FOR COPYING, PRINTING, SCANNING – EVEN WHEN ON THE MOVE VIA WIFI* – OR FAXING*. HIGH PAPER CAPACITIES, PROFESSIONAL PAPER MANAGEMENT AND AN ARRAY OF CONFIGURATION OPTIONS PROVIDE THE IDEAL CONDITIONS TO COMPLETE LARGE-SCALE ORDERS QUICKLY AND EFFICIENTLY.

LOOKING FOR AN EXTRA PERFORMANCE BOOST? THEN CONFIGURE YOUR SYSTEM INDIVIDUALLY TO MEET YOUR SPECIFIC NEEDS WITH OPTIONAL HARDWARE AND SOFTWARE SOLUTIONS.



HIGHLIGHTS:



Maximum productivity: It's easy to complete large-scale print jobs such as brochures, form letters, budgets or folder contents with indexes. Take advantage of professional finishing* and you will give your print jobs an excellent finishing touch.




Professional paper management: Benefit from the high paper capacities of up to 7,650 pages from 8 paper feeds* for various types of paper and replace your toner cartridges during ongoing operations. Print special formats up to A3+ as well as intermediate formats from the cassette, paper weights up to 300 g/m², tab sheets and banner paper, and define up to 50 dividers in just one print job.



Create documents quickly: High-speed outputs of up to 80 A4 pages/minute, to 40 A3 pages/minute (8055i), 100% duplex productivity, short warm-up times and output of the first copy after a mere 5.2/4.7 seconds (6555i/8055i) ensure that complex tasks can be completed rapidly. The standard dual scan original feeder scans up to 100 single-sided A4 original pages/minute.



Customised functionality: It is easy to integrate optional software solutions for scanning, productivity and security using the HyPAS interface – all in exact accordance with your individual needs. Save time and money with solutions for Follow-Me-Printing* within the network or for creating text-searchable documents when scanning.

DIGITAL 
MULTIFUNCTIONAL SYSTEM
6555i / 8055i
Copy / Print / Scan / Fax
A3

General		Print system		Optional fax system (W) B	
Type	Console Unit	Type	Integrated within the system	Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi
Function	Copy, print, scan, optional: fax	Print format	A6R-A3+	Fax memory	12 MB (max 120 MB)
Print technology	Laser b/w	Print resolution	600 x 600 dpi, 9,600 x 600 dpi level	Abbreviated dial	2,000 numbers
Original format	max A3 from platen glass	Processor	Freescale QorIQ P1022 (Dual Core) 1.067 MHz	One touch dial	1,000 numbers
Original feeder	Document processor with simultaneous duplex scanning (A6R-A3, capacity: 270 sheet A4, paper weight 35-220 g/m ²)	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host	Group dial	500 numbers
Copy/print speed	6555i: max 65 A4 pages/min and max 32 A3 pages/min 8055i: max 80 A4 pages/min and max 40 A3 pages/min	Network protocols	TCP/IP, IPX/SPX, Net BEUI	Operating systems	Windows XP, Vista, Windows 7/8/8.1, Server 2003/2008 R2/2012 R2
1st page (copy/print)	5.2/5.8 seconds* (6555i), 4.7/5.4 seconds* (8055i)	Operating systems	Windows XP, Vista, Windows 7/8/8.1, Server 2003/2008 R2/2012 R2, Novell NetWare, Linux, Mac OS 10.4	Functions	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for parallel transmission and reception
Warm-up time	30 seconds	Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe	Options	
Copy resolution	600 x 600 dpi, 9,600 x 600 dpi level	Functions	PDF-direct printing, printing of e-mails, private printing, barcode printing	Finisher	DF-790 (C) (capacity: 4,000 sheet A4, stapling max 65 sheet A4), PH-7C hole punch unit for DF-790 (C), BF-730 brochure module for DF-790 (C) (max 16 sheet saddle stitching and folding A4/A3, tri-folding max 5 sheet A4), MT-730 (B) multi tray for DF-790 (C)
Greyscales	256	Scan system		Paper feed	PF-730 (B) (2 x 500 sheet universal cassettes (A5R-A3+)), PF-740 (B) (2 x 1,500 sheet large capacity cassettes (A4)), PF-780 (B) (500 sheet multi-purpose cassette (A5R-A3+), required if PF-730 (B)/PF-740 (B) is installed), PF-770 (B) (3,000 sheet large capacity tray (A4), side deck)
Paper feed	2 x 500 sheet universal cassettes (A5R-A3+ [max 305 x 457 mm]), 2 x 1,500 sheet large capacity cassettes (A4), 150 sheet multi-bypass (A6R-A3+, Banner [305 x 457 mm])	Scan type	CCD colour and b/w	Other options	Data security kit (E), Internet fax kit (A), Printed document guard kit (B), Card authentication kit (B), Card reader holder (E), Keyboard holder (C), Banner guide (A), UG-33 ThinPrint® kit, UG-34 Emulation option kit, IB-50 Gigabit Ethernet card, IB-51 WLAN card, Copy tray type D
Paper weights	Universal cassette 60-256 g/m ² , multi-bypass 60-300 g/m ² , duplex 60-256 g/m ²	Scan format	max A3	* Depending on operating status.	
Paper output	250 sheet A4 (upper tray), 100 sheet (lower tray) with Copy tray type D	Scan speed	b/w: max 100/180 A4 originals/min (simplex/duplex), colour: max 70/100 A4 originals/min (simplex/duplex) (300 dpi)	** For copy, print, scan, fax.	
System memory	3 GB RAM, 320 GB HDD**	Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi	Specifications subject to change without notice.	
Continuous copying	1-9,999 copies	Scan mode	Photo, text, photo/text, OCR	Image shows machine with optional accessories.	
Zoom	25%-400% in steps of 1 %	File types	TIFF, PDF, PDF/A, JPEG, XPS	The 6555i and 8055i are manufactured in accordance with the requirements of the Energy Star Program.	
Functions	Adjustable touch screen, duplex, 1,000 management codes, multi tasking controller, direct printing from USB stick, etc.	Interface	10/100/1000BaseTX		
Dimensions/Weight		Network protocol	TCP/IP		
Dimensions	1,347 x 1,039 x 723 mm (H x W x D)	Operating systems	Windows XP, Vista, Windows 7/8, Server 2003/2008 R2/2012		
Weight	approx. 155 kg	Functions	Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan (Windows Vista, Windows 7/8, Server 2008 R2/2012), SMTP authentication, LDAP, PDF compression and encryption		
Environment		Optional fax system (W) B			
Mains voltage	220/240 V, 50/60 Hz	Compatibility	Super G3		
Power consumption	approx. 2,400 max, approx. 1,210 W (6555i)/1,410 W (8055i) in operation, approx. 300 W in stand-by mode, approx. 11 W in sleep mode	Original format	max A3		
Safety	GS/TÜV, CE	Modem speed	33.6 kbps		
		Transmission speed	3 seconds or less using JBIG		
		Compression method	JBIG, MMR, MR, MH		

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.



Your UTAX dealer