

NO FRILLS, JUST OUTPUT!

NOW YOU CAN SIMPLY PASS ON THE PRINTING PRESSURE.
 THE NEW BENCHMARK IN HIGH PRODUCTIVITY FOR LARGE PRINT JOBS IN
 COLOUR AND B/W.



Authorised access to all print jobs thanks to the card reader, at any time and anywhere



The intuitive LC display panel: simplicity in its most beautiful form



Great printing results in all formats: from A6R to A3+

HIGHLIGHTS:

- **Improved cost efficiency:** We ensure a high availability of all processes at any time by reducing actions to the essentials.
- **Diverse range of media:** The paper capacity is impressively high – up to 7,650 pages with paper weights of 60–300 g/m² in A6R to A3+ formats from eight paper sources*. This equips you well for any work environment.
- **Well-organised:** An extremely high output capacity of up to 1,450 pages holds your print jobs cleanly and neatly.
- **High productivity:** When using the finisher* you obtain almost full productivity.
- **Reliable data protection:** Data encryption and secure deletion of print jobs; access via PIN codes or ID cards, as well as 128-bit AES encryption.
- **Direct printing of PDFs:** Now also available in the current 1.7 version for better printing results (e. g. for transparencies).



Small, but can do big things: The P-C4580DN and P-C5580DN will surprise you with their compact design and high productivity even with different paper weights, whether high-grade brochures* or folded invoices*. The mailbox* guarantees your print jobs will never again get mixed up even at central locations.



Your daily routine is made simple by the intelligent automation. Print jobs are easily stored and sorted using the new document box key. You can call them up again at any time just by pushing a button. The status monitor keeps you informed of toner and paper levels all the time – for perfect printing, always.



COLOUR PRINTER / A3

P-C4580DN
P-C5580DN

P-C4580DN

P-C5580DN

TECHNICAL DATA

General		General		Options	
Type	Desktop	Processor	PowerPC 750GL/750 MHz	Finisher	DF-790 (B) (capacity: 4,000 sheets A4, stapling max 65 sheets A4), DF-770 (B) (capacity: 1,000 sheets A4, stapling max 50 sheets A4), PH-7C punch unit for DF-790 (B)/770 (B), BF-730 brochure module for DF-790 (B) (saddle stitching and folding max 16 sheets A4/A3, tri-folding max 5 sheets A4), MT-730 (B) multi tray for DF-790 (B), AK-735 attachment kit for DF-790 (B)/770 (B)
Function	Print	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2), CF slot	Paper tray	MT-730 (B), AK-736 for MT-730 (B)**
Print technology	Laser colour and b/w	Network protocols	TCP/IP, Net BEUI, EtherTalk	Paper feed	PF-730 (2 x 500 sheet universal large [A5R-A3+]), PF-740 (3,000 sheet capacity tray [A4]), PF-780 (500 sheet multi purpose cassette [A5R-A3+], required if two PF-730/PF-740 are installed, PF-770 (3,000 sheet large capacity tray (A4), side deck), Banner Guide (A)
Print format	A5R-A3+	Operating systems	Windows XP, Vista, Windows 7, Server 2003/2008 R2, Novell NetWare, Linux, Mac ex OS X	Other options	Data Security Kit (E), Card Authentication Kit (B), Card Reader Holder (B), UG-33 ThinPrint® Kit, UG-34 Emulation Option Kit, IB-50 Gigabit Ethernet card
Print speed	P-C4580DN: max 45 A4 pages/min and max 22 A3 pages/min in colour and b/w P-C5580DN: max 50 A4 pages/min and max 25 A3 pages/min in colour and max 55 A4 pages/min and max 27 A3 pages/min in b/w	Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc		
1st page	Colour: 6.6 seconds*, b/w: 5.4 seconds* (P-C4580DN), Colour: 6.2 seconds*, b/w: 4.9 seconds* (P-C5580DN)	Functions	PDF direct print, direct print from USB stick, e-mail print, internet print, private print, barcode print, job saving, print-on-demand, toner save mode		
Warm-up time	30 sec.	Dimensions/Weight			
Print resolution	600 x 600 dpi, 9,600 x 600 dpi level	Dimensions	747 x 668 x 787 mm (H x W x D)		
Greyscales	256	Weight	approx. 107 kg		
Paper feed	2 x 500 sheet universal cassettes (A5R-A3+ [max 305 x 457 mm]), 150 sheet multi bypass (A6R-A3+, banner [305 x 1,219 mm])	Environment			
Paper weights	Universal cassette 60-256 g/m ² , multi bypass 60-300 g/m ² , duplex 60-256 g/m ²	Mains voltage	220/240 V, 50/60 Hz		
Paper output	500 sheet A4	Power consumption	approx. 1,800 W max, approx. 1,140 W (P-C4580DN)/1,210 W (P-C5580DN) in operation, approx. 170 W in stand-by mode, approx. 15 W in sleep mode		
Job Separator	Standard, 2 x 250 sheet A4	Noise level	approx. 72.5 dB(A) (P-C4580DN)/74 dB(A) (P-C5580DN) in operation, approx. 40 dB(A) in stand-by mode (ISO 7779/9296)		
System memory	1,024 MB RAM (max 2,048 MB RAM), 160 GB hard disc	Safety	GS/TÜV, CE		

* Depending on operating status.

** When directly installed on the system.

Specifications subject to change without notice.
 Image shows machine with optional accessories.

The P-C4580DN and P-C5580DN are manufactured in accordance with the requirements of the Energy Star Program.



UTAX GmbH has been a trade mark for professional office technology since 1961. As the partner of specialist traders and small and medium-sized businesses, we specialise in the distribution and integration of printing, copying and multifunctional systems in corporate IT. Our clients' commercial success and strategic company objectives play a central role for us. We support them with integrated document management concepts. With the MDS solution UTAX smart, output systems can be controlled irregardless of the manufacturer and the infrastructure can be optimised in line with demands.

UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trademarks of UTAX GmbH. All other brand names referred to are registered trademarks of the respective manufacturers.

Your UTAX dealer